



## MT2010S™ **10.1" RUGGED TABLET** – Light and thin, but still rugged

You need a tablet for your field service or warehouse employees that is rugged enough to stand up to the abuse every day and can run the applications and software you are already using? That is where the MT2010S rugged tablet comes in.

The MT2010S withstands a 4-foot drop without a problem and runs full version of Windows. The large display of the 10.1-inch projected capacitive touchscreen is sunlight-readable so you can work outside as easily as inside. No more squinting at a small, difficult-to-read screen.

### **Tired of dealing with the repair costs of consumer grade tablets?**

The MT2010S is IP65 dustproof and water resistant and will work in temperatures of -20 to +50 °C (-4 to +122 °F).

With light weight and no more than 0.75 inch thick, you can

easily mount the MT2010S in your field service technicians' trucks where they can remove it to use on the job.

### **Get everything you need, and nothing you don't**

The MT2010S rugged tablet can be customized to your specifications. Example of customizations include:

- Add more storage to your computers if you need it to run certain applications.
- Modify the operating system to increase its security.
- Install safety features that reduce the risk of data loss and corruption.

# Because it Works!™

# MT2010S™ Product Specifications

## Base unit

<b>Display</b>	10.1" (1920 x 1200)
	800:1 Contrast
	800 NIT (typ.) Brightness
	Multi-touch projective capacitive touch
	Optical bonding for sunlight viewability
<b>Memory</b>	8GB
<b>Processor</b>	Intel® Core i5-7200U Kaby lake 2.5GHz

## Storage

<b>Onboard</b>	64GB SSD (optional up to 512GB)
<b>Expansion</b>	microSDXC-card (up to 128 GB)

## RF Options

<b>Bluetooth</b>	v 4.2
<b>GNSS</b>	GPS / GLONASS / BeiDou
<b>WLAN</b>	802.11 a/b/g/n/ac
<b>WWAN</b>	Optional 4G (LTE, HSPA+, GSM/GPRS/EDGE, EV-DO Rev A, 1x RTT)

## Interfaces

<b>Audio</b>	1x Built-in dual digital mic with noise cancellation
	2x 1W Speaker
<b>Camera</b>	Front: 2.0 MP webcam
	Rear: 8.0 MP auto focus w. LED flash
<b>Data Capture</b>	1D/2D barcode reader (optional)
	HF RFID reader 13.56 MHz (optional)
<b>Indicators</b>	4x LED (power, battery, HDD, RF)
<b>Keys</b>	1x Home
	1x Power
	2x Programmable function keys
	2x Volume keys
<b>Ports</b>	1x 19-pin Docking connector
	1x Line out/Mic in
	1x Micro HDMI
	1x Micro SD Slot
	1x Power Jack
	1x USB 3.0 Type A
	1x USB 3.0 Type C

## Sensors

<b>Sensors</b>	Digital compass
	G-sensor
	Light sensor

## Power Supply

<b>Adapter</b>	AC 110 ~ 240 V, 50 ~ 60 Hz / 19 VDC
<b>Battery</b>	7.4V, 5140 mAh Li-Polymer Battery (extended battery 7.4V, 10280 mAh available)
	8 hours (depending on usage)
	Hot-swappable
<b>Input</b>	12 - 19 VDC

## Security

<b>Lock</b>	Kensington lock
<b>Mobile Device Management</b>	SOTI Mobicontrol compatible, available upon request
<b>TPM</b>	V 2.0

## Operating System

<b>Windows</b>	Windows 10
----------------	------------

## Physical Characteristics (with standard battery)

<b>Dimensions</b>	271.67mm (w) x 198.2mm (h) x 21mm (d) 10.7 inch (w) x 7.8 inch (h) x 0.83 inch (d)
<b>Weight</b>	1.25 kg / 2.7 lb

## Environment

<b>Drop</b>	MIL-STD-810G (multiple 4-foot drop to concrete)
<b>Dust and water</b>	IP65
<b>Humidity</b>	10%–90% RH, non-condensing
<b>Operating temp.</b>	-20°C to 60°C / 4°F to 158°F (AC mode)
	-10°C to 50°C / 14°F to 122°F (battery mode)
<b>Shock</b>	MIL-STD-810G
<b>Storage temp.</b>	-20°C to 60°C / 4°F to 158°F
<b>Vibration</b>	MIL-STD-810G

**JLT Mobile Computers**

**Head Office:** Isbjörnsvägen 3, SE-352 45 Växjö, SWEDEN  
**Sales Office:** Norrtullsgatan 6, Floor 5, SE-113 29 Stockholm, SWEDEN  
**Phone:** +46 470 53 03 00 **Mail:** info@jltmobile.com

**North America:** 7402 West Detroit Street, Suite 150 Chandler, Arizona 85284, USA  
**Toll free US:** 844-705-4200 **Intl Phone:** +1 480 705 4200 **Fax:** +1 480 397 1214 **Mail:** USsales@jltmobile.com  
[www.jltmobile.com](http://www.jltmobile.com)

