



MT2010™ **10.1" RUGGED TABLET** – Light and thin, but still rugged

You need a tablet for your field service or warehouse employees that is rugged enough to stand up to the abuse every day and can run the applications and software you are already using? That is where the MT2010 rugged tablet comes in.

The MT2010 withstands a 4-foot drop without a problem and runs full version of Windows. The large display of the 10.1-inch projected capacitive touchscreen is sunlight-readable so you can work outside as easily as inside. No more squinting at a small, difficult-to-read screen.

Tired of dealing with the repair costs of consumer grade tablets?

The MT2010 is IP65 dustproof and water resistant and will work in temperatures of -20 to +50 °C (-4 to +122 °F). With light weight and no more than 0.75 inch thick, you can

easily mount the MT2010 in your field service technicians' trucks where they can remove it to use on the job.

Get everything you need, and nothing you don't

The MT2010 rugged tablet can be customized to your specifications. Example of customizations include:

- Add more storage to your computers if you need it to run certain applications.
- Modify the operating system to increase its security.
- Install safety features that reduce the risk of data loss and corruption.

Because it Works!™

MT2010™ Product Specifications

Base unit

Processor	Intel® Celeron® Quad Core N2930 1.83 GHz
Memory	4GB DDR3L 1600 MHz (up to 8GB)
Display	10.1" (1920 x 1200) 800:1 Contrast 700 NIT (typ.) Brightness 16.7M (6-bit + HFRC) Color Optical bonding for sunlight viewability Multi-touch Projective Capacitive Touch

Storage

mSATA	64GB MLC SSD (up to 256GB)
--------------	----------------------------

RF Options

Radio	WLAN 802.11 a/b/g/n Bluetooth v4.0+ Class I Optional 4G (LTE, HSPA+, GSM/GPRS/EDGE, EV-DO Rev A, 1xRTT) or optional 3G (HSPA+, GSM/GPRS/EDGE) GPS U-blox Neo-6Q / GLONASS
--------------	--

Interfaces

Ports	Right I/O Connectors 1x USB 3.0 1x Micro HDMI (optional) 1x Micro SD Slot 1x 30-pin Combo Conn. (Giga-LAN or RS232) 1x Line out/Mic in 1x DC jack Downside I/O Connectors 1x Extension port 1x Docking Connector
Audio	1x Built-in Mic 2x 1W Speaker
Camera	Rear: 5.0 MP auto focus w. LED flash Front: 2.0 MP
Data Capture	Short range 1D/2D bar code reader (optional) (not for use w. HF RFID)
Keys	1x Power 1x Home 2x Programmable function keys 2x Volume keys
LED Indicators	Power, Battery, HDD, RF

Sensors

	Light sensor
	G sensor
	Gyrometer
	E-compass

Power Supply

Input	12 - 19 VDC
Battery	Hot-swappable 7.4 V typ., 5140 mAh Li-Polymer (2S1P) or optional 7.4 V typ., 10280 mAh Li-Polymer (2S2P) 8 hours (depending on usage)
Adapter	AC 110 ~ 240V, 50 ~ 60 Hz / 19VDC

Security

Password	For user and hard disk lock
TPM	V1.2
Lock	Kensington lock slot
Other	Computrace® theft protection support

Operating System

Windows	Windows 10
----------------	------------

Physical Characteristics (with standard battery)

	271.8mm (w) x 197.2mm (h) x 19mm (d) 10.7 inch (w) x 7.76 inch (h) x 0.75 inch (d)
Weight	1.2 kg / 2.7 lb

Environment

Operating temp.	-20 to +50 °C / -4 to +122 °F (battery)
Storage temp.	-30 to +70 °C / -22 to +158 °F
Humidity	10%–90% RH, non-condensing
Dust and water	IP65
Vibration	MIL-STD-810G
Shock	MIL-STD-810G
Drop	MIL-STD-810G (multiple 4-foot drop to concrete)

JLT Mobile Computers

Head Office: Isbjörnsvägen 3, SE-352 45 Växjö, SWEDEN
Sales Office: Medborgarplatsen 3, Plan 8, SE-118 26 Stockholm, SWEDEN
Phone: +46 470 53 03 00 **Fax:** +46 470 445 29 **Mail:** info@jltmobile.com
North America: 7402 West Detroit Street, Suite 150 Chandler, Arizona 85284, USA
Toll free US: 844-705-4200 **Intl Phone:** +1 480 705 4200 **Fax:** +1 480 397 1214 **Mail:** USsales@jltmobile.com
www.jltmobile.com

