



MT2010™ **10.1" RUGGED TABLET** – Light and thin, but still rugged

You need a tablet for your field service or warehouse employees that is rugged enough to stand up to the abuse every day and can run the applications and software you are already using? That is where the MT2010 rugged tablet comes in.

The MT2010 withstands a 4-foot drop without a problem and runs full version of Windows. The large display of the 10.1-inch projected capacitive touchscreen is sunlight-readable so you can work outside as easily as inside. No more squinting at a small, difficult-to-read screen.

Tired of dealing with the repair costs of consumer grade tablets?

The MT2010 is IP65 dustproof and water resistant and will work in temperatures of -20 to +50 °C (-4 to +122 °F). With light weight and no more than 0.75 inch thick, you can

easily mount the MT2010 in your field service technicians' trucks where they can remove it to use on the job.

Get everything you need, and nothing you don't

The MT2010 rugged tablet can be customized to your specifications. Example of customizations include:

- Add more storage to your computers if you need it to run certain applications.
- Modify the operating system to increase its security.
- Install safety features that reduce the risk of data loss and corruption.

Because it Works!™

MT2010™ Product Specifications

Base unit

Display	10.1" (1920 x 1200)
	800:1 Contrast
	800 NIT (typ.) Brightness
	Multi-touch projective capacitive touch
	Optical bonding for sunlight viewability
Memory	4GB DDR4 (up to 8GB)
Processor	Intel® Core i5-7200U Kaby lake 2.5GHz

Storage

Onboard	64GB SSD (optional up to 512GB)
Expansion	microSDXC-card (up to 128 GB)

RF Options

Bluetooth	v 4.2
GNSS	GPS / GLONASS / BeiDou
WLAN	802.11 a/b/g/n/ac
WWAN	Optional 4G (LTE, HSPA+, GSM/GPRS/EDGE, EV-DO Rev A, 1x RTT)

Interfaces

Audio	1x Built-in dual digital mic with noise cancellation
	2x 1W Speaker
Camera	Front: 2.0 MP webcam
	Rear: 8.0 MP auto focus w. LED flash
Data Capture	1D/2D barcode reader (optional)
	HF RFID reader 13.56 MHz (optional)
Indicators	4x LED (power, battery, HDD, RF)
Keys	1x Home
	1x Power
	2x Programmable function keys
	2x Volume keys
Ports	1x 19-pin Docking connector
	1x Line out/Mic in
	1x Micro HDMI
	1x Micro SD Slot
	1x Power Jack
	1x USB 3.0 Type A
	1x USB 3.0 Type C

Sensors

Sensors	Digital compass
	G-sensor
	Light sensor

Power Supply

Adapter	AC 110 ~ 240 V, 50 ~ 60 Hz / 19 VDC
Battery	7.4V, 5140 mAh Li-Polymer Battery (extended battery 7.4V, 10280 mAh available)
	8 hours (depending on usage)
	Hot-swappable
Input	12 - 19 VDC

Security

Lock	Kensington lock
Mobile Device Management	SOTI Mobicontrol compatible, available upon request
TPM	V 2.0

Operating System

Windows	Windows 10
----------------	------------

Physical Characteristics (with standard battery)

Dimensions	271.67mm (w) x 198.2mm (h) x 21mm (d) 10.7 inch (w) x 7.8 inch (h) x 0.83 inch (d)
Weight	1.25 kg / 2.7 lb

Environment

Drop	MIL-STD-810G (multiple 4-foot drop to concrete)
Dust and water	IP65
Humidity	10%–90% RH, non-condensing
Operating temp.	-20°C to 60°C / 4°F to 158°F (AC mode)
	-10°C to 50°C / 14°F to 122°F (battery mode)
Shock	MIL-STD-810G
Storage temp.	-20°C to 60°C / 4°F to 158°F
Vibration	MIL-STD-810G

JLT Mobile Computers

Head Office: Isbjörnsvägen 3, SE-352 45 Växjö, SWEDEN
Sales Office: Medborgarplatsen 3, Plan 8, SE-118 26 Stockholm, SWEDEN
Phone: +46 470 53 03 00 **Mail:** info@jltmobile.com

North America: 7402 West Detroit Street, Suite 150 Chandler, Arizona 85284, USA
Toll free US: 844-705-4200 **Intl Phone:** +1 480 705 4200 **Fax:** +1 480 397 1214 **Mail:** USsales@jltmobile.com
www.jltmobile.com

